

C19 to C20 Heavy-Duty Extension Cord - 20A, 250V, 12 AWG, 2 ft., Black, 6-Pack

MODEL NUMBER: P036-002-6





C19 to C20 20A heavy-duty extension cables connect high-output devices with C19/C20 power connectors, including blade server chassis.

Features

20A C20-to-C19 Power Cable for Network Devices That Require a Heavy-Gauge ConnectionThis package of six heavy-duty extension cords features 12 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. These cords can be used to connect servers, routers, network switches and blade server enclosures to a UPS system or PDU or replace or upgrade the standard power cords provided by the devices' manufacturers. The two-foot length helps reduce cable clutter and minimize the risk of tripping.

Highlights

- Recommended for powering servers, routers and other highoutput network devices
- 2 ft. length allows flexibility in placing devices, while avoiding cable clutter
- C20 to C19 cord replaces or upgrades standard power cord provided by manufacturer
- Thick 12 AWG wire gauge manages high power levels required for larger equipment

Applications

- Connect devices like computers, servers and monitors to a PDU up to 2 ft. away in your data center
- Extend existing power connections up to 2 ft. to more easily place devices or reach a power source in a rack
- Update or replace the standard power cords provided by the original manufacturers

Package Includes

• (6) C19 to C20 Heavy-Duty Extension Cords, 2 ft., Black

Specifications

OVERVIEW	
UPC Code	037332180674
Country/Region	North America
Power Cord Application	Server; PDU; UPS





INPUT	
Maximum Input Amps	20
Cable Length (ft.)	2
Cable Length (m)	0.6
Voltage Compatibility (VAC)	250
PHYSICAL	
Power Cord Jacket Type	SJT
Wire Gauge (AWG)	12
Wire Gauge (OD - mm²)	3.31
Shipping Dimensions (hwd / in.)	8.00 x 12.00 x 9.50
Shipping Dimensions (hwd / cm)	20.32 x 30.48 x 24.13
Shipping Weight (lbs.)	3.20
Shipping Weight (kg)	1.45
Color	Black
Number of Conductors	3
CONNECTIONS	
Side A - Connector 1	IEC-320-C20
Side B - Connector 1	IEC-320-C19
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies