View on mating side

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
d	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
c	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
b	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
a	X	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	Y	X	A	A

A = 125 STANDARD CONTACTS L=2
X = 2 FMLB CONTACTS L=2
Y = 1 LMFB CONTACT L=2

S = 128 TOTAL NUMBER OF CONTACTS

Marking	Standard
Performance level	G2/0 = Contact area perform. level 2 / Termination tin
Flux proof	NO
Fixing clip	NO
Dimensions	SDA-85015-0001 SHT 1
Technical Data	PS-85013-0002

Y	G2/0	a29
X	G2/0	a1, a30
A	G2/0	a2-a28, a31-a32, b1-b32, c1-c32, d1-d32
Contact symbol	Perform. level	Contact position number

EC NO: I2004-0363
DRWN: SSUDHIR 2004/03/11
CH'KD: GJLOWE 2004/03/11
APPR: GJLOWE 2004/04/26
DESCRIPTION
A
REV

QUALITY SYMBOLS
▼ = 0
▽ = 0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---
ANGULAR ±---°		

DRAFT WHERE APPLICABLE
MUST REMAIN WITHIN DIMENSIONS

SCALE ---
DESIGN UNITS METRIC
THIRD ANGLE PROJECTION
REVISE ON CAD ONLY
DIMENSION STYLE MM ONLY
DRAWN BY SSUDHIR DATE 2004/03/11
CHECKED BY GJLOWE DATE 2004/03/11
APPROVED BY GJLOWE DATE 2004/03/11

TITLE
128 POS MALE CONNECTOR
ACC DIN41612 STYLE R
CONTACTS ARRANGEMENT

molex MOLEX INCORPORATED

MATERIAL NO. 85015-9006
DOCUMENT NO. SDA-85015-9006
SHEET NO. 1 OF 1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

A3